

Navy and Coast Guard

Navy

Garlock manufactures numerous expansion joints in accordance with U.S. Navy specifications.

Style 9278 EZ-FLO® is designed to meet the requirements of ASTM F1123, and is constructed of neoprene and polyamide. Retaining rings must be galvanized in accordance with the specification. Hydrostatic testing may be required and is performed in-house at our Palmyra, New York, facility.

Style 7706 S-type (as pictured) has been developed specifically for submarine service.

Other styles are available per application. Consult the factory for specific designs.



Coast Guard

Garlock expansion joints certified to Coast Guard Specification ASTM-F1123 are:

- Style 206 EZ-FLO®
- Style 204 CL 11
- GARFLEX® 8100

All of these styles must have a neoprene cover (with no paint). Coast Guard certification should be requested at the time of quotation or order.



WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Garlock. Failure to select the proper sealing products could result in property damage and/or serious personal injury.

Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing.

While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

GARLOCK is a registered trademark for packings, seals, gaskets, and other products of Garlock.